# AVT204B















### 4CH HD CCTV DVR

## FEATURES

#### Free P2P Cloud EaZy Networking\*

- Cloud EaZy Networking available to connect this device to Internet automatically in three steps with our free mobile app, EagleEyes.
- The "Buddy" feature to share the device access permission to other people.
- Device login / out notifications reported.



### <u>Push Video & Push Status -</u> Active Event Notification with EagleEyes App

- Push Video to send instant notifications for an alarm event when an alarm device is connected to the DVR.
- Push Status to send instant notifications for system events, such as video loss or HDD data removal.



#### **Intelligent Video Analysis**

The Smart TVI DVR supports IVS (Intelligent Video System) to set a virtual detection line for people counting, virtual fence, and one-way pass. It's the advanced usage for motion detection to not only record but also summarize the detection data for further analysis.



#### **HD Video Recording**

- HD real-time recording brings users clear images while video recording and playback
- 1920\*1080 Full HD video output service, giving the best image quality on LCD / LED monitors

#### Video Backup

Regular backup could be configured to automatically copy video footages to the specified location (USB drive or FTP) at the specified time.

#### **External Disk Array Support for More Video Storage**

eSATA interface built-in to connect a disk array (RAID 0 / 1 / 5 / 6 / 0 + 1 / 1 + 0 ) for more video storage.

#### **Remote Surveillance**

- Fully compatible with iOS and Android devices, and Internet Explorer on Windows operating system
- CMS Lite for 32 devices central management
- Applicable also to Apple's media player, QuickTime.

# SPECIFICATIONS

| Video System   |             | NTSC / PAL (auto detection)   |  |
|--|-------------|---|--|
| Video Compression Format   |             | H.264   |  |
| Video Input  |             | 4 channels (Composite video signal 1 Vp-p 75Ω BNC)  |  |
| Video Output   | BNC         | YES   |  |
|  | VGA         | YES   |  |
| HDMI   |             | YES   |  |
| ▼ Record & Bac   | kup         |   |  |
| Maximum Recording  |             | P 1920 x 1080 pixels with 60 IPS  |  |
| 720P<br>QHD<br>Frame<br>Field<br>CIF   |             |   |  |
|  |             |   |  |
|  |             |   |  |
|  |             |   |  |
|  |             |   |  |
|  |             | 352×240 pixels with 120 IPS <ntsc> / 352×288 pixels with 100 IPS <pal></pal></ntsc>   |  |
| Recording Mode   |             | Manual / Timer / Motion / Alarm / Remote  |  |
| Pre-alarm Recording  |             | YES   |  |
| Playback Channel   |             | 4CH   |  |
| Quick Search   |             | Time / Motion / Alarm search mode   |  |
| Backup Device  |             | USB 2.0 drive / Network   |  |
| Regular Backup   |             | YES   |  |
| <b>V</b> Audio   |             |   |  |
| Audio Input  |             | 1 audio input   |  |
| Audio Output   |             | 1 audio output (Mono)   |  |
| ▼ General  |             |   |  |
| Hard Disk Storage**  |             | Up to 2 SATA HDDs   |  |
| SATA Interface   |             | YES   |  |
| eSATA Interface  |             | YES (For external disk array connection)  |  |
| Image Quality Setting  |             | SUPER BEST / BEST / HIGH / NORMAL   |  |
| USB Mouse Control  |             | YES   |  |
| Motion Detection Area  |             | YES   |  |
| 141011011 POLOULUII AI C   | a           |   |  |
|  |             | 16 × 12 grids per channel   |  |
| Motion Detection Sen   |             | 16 × 12 grids per channel 3 adjustable parameters for accurate detection  |  |
| Motion Detection Sen<br>Event Notification   |             | 16 × 12 grids per channel 3 adjustable parameters for accurate detection Push Video / Push Status / FTP / E-Mail  |  |
| Motion Detection Sen<br>Event Notification<br>Picture Zoom   |             | 16 × 12 grids per channel 3 adjustable parameters for accurate detection Push Video / Push Status / FTP / E-Mail 2X digital zoom  |  |
| Motion Detection Sen<br>Event Notification<br>Picture Zoom<br>PTZ Control  |             | 16 × 12 grids per channel 3 adjustable parameters for accurate detection Push Video / Push Status / FTP / E-Mail 2X digital zoom YES  |  |
| Motion Detection Sen<br>Event Notification<br>Picture Zoom<br>PTZ Control<br>Alarm I/O   |             | 16 × 12 grids per channel 3 adjustable parameters for accurate detection Push Video / Push Status / FTP / E-Mail 2X digital zoom YES 4 inputs, 1 output   |  |
| Motion Detection Sen<br>Event Notification<br>Picture Zoom<br>PTZ Control<br>Alarm I/O<br>RS485  |             | 16 × 12 grids per channel 3 adjustable parameters for accurate detection Push Video / Push Status / FTP / E-Mail 2X digital zoom YES 4 inputs, 1 output YES   |  |
| Motion Detection Sen<br>Event Notification<br>Picture Zoom<br>PTZ Control<br>Alarm I/O<br>RS485<br>IR Remote Control   | sitivity    | 16 × 12 grids per channel 3 adjustable parameters for accurate detection Push Video / Push Status / FTP / E-Mail 2X digital zoom YES 4 inputs, 1 output YES YES (IR receiver built-in)  |  |
| Motion Detection Sen<br>Event Notification<br>Picture Zoom<br>PTZ Control<br>Alarm I/O<br>RS485<br>IR Remote Control<br>Key Lock (Password I   | sitivity    | 16 × 12 grids per channel 3 adjustable parameters for accurate detection Push Video / Push Status / FTP / E-Mail 2X digital zoom YES 4 inputs, 1 output YES YES (IR receiver built-in) YES  |  |
| Motion Detection Sen<br>Event Notification<br>Picture Zoom<br>PTZ Control<br>Alarm I/O<br>RS485<br>IR Remote Control<br>Key Lock (Password I<br>User Level   | Protection) | 16 × 12 grids per channel 3 adjustable parameters for accurate detection Push Video / Push Status / FTP / E-Mail 2X digital zoom YES 4 inputs, 1 output YES YES (IR receiver built-in) YES 4 user levels for different access privilege   |  |
| Motion Detection Sen<br>Event Notification<br>Picture Zoom<br>PTZ Control<br>Alarm I/O<br>RS485<br>IR Remote Control<br>Key Lock (Password I<br>User Level<br>Video Loss Detection   | Protection) | 16 × 12 grids per channel 3 adjustable parameters for accurate detection Push Video / Push Status / FTP / E-Mail 2X digital zoom YES 4 inputs, 1 output YES YES (IR receiver built-in) YES 4 user levels for different access privilege YES   |  |
| Motion Detection Sen Event Notification Picture Zoom PTZ Control Alarm I/O RS485 IR Remote Control Key Lock (Password I User Level Video Loss Detection Camera Title   | Protection) | 16 × 12 grids per channel 3 adjustable parameters for accurate detection Push Video / Push Status / FTP / E-Mail 2X digital zoom YES 4 inputs, 1 output YES YES (IR receiver built-in) YES 4 user levels for different access privilege YES Supports up to 25 letters   |  |
| Motion Detection Sen Event Notification Picture Zoom PTZ Control Alarm I/O RS485 IR Remote Control Key Lock (Password I User Level Video Loss Detection Camera Title Video Adjustable  | Protection) | 16 × 12 grids per channel 3 adjustable parameters for accurate detection Push Video / Push Status / FTP / E-Mail 2X digital zoom YES 4 inputs, 1 output YES YES (IR receiver built-in) YES 4 user levels for different access privilege YES Supports up to 25 letters Hue / Saturation / Contrast / Brightness  |  |
| Motion Detection Sen Event Notification Picture Zoom PTZ Control Alarm I/O RS485 IR Remote Control Key Lock (Password I User Level Video Loss Detection  | Protection) | 16 × 12 grids per channel 3 adjustable parameters for accurate detection Push Video / Push Status / FTP / E-Mail 2X digital zoom YES 4 inputs, 1 output YES YES (IR receiver built-in) YES 4 user levels for different access privilege YES Supports up to 25 letters   |  |
| Motion Detection Sen Event Notification Picture Zoom PTZ Control Alarm I/O RS485 IR Remote Control Key Lock (Password I User Level Video Loss Detection Camera Title Video Adjustable Date Display Format  | Protection) | 16 × 12 grids per channel 3 adjustable parameters for accurate detection Push Video / Push Status / FTP / E-Mail 2X digital zoom YES 4 inputs, 1 output YES YES (IR receiver built-in) YES 4 user levels for different access privilege YES Supports up to 25 letters Hue / Saturation / Contrast / Brightness  |  |
| Motion Detection Sen Event Notification Picture Zoom PTZ Control Alarm I/O RS485 IR Remote Control Key Lock (Password I User Level Video Loss Detection Camera Title Video Adjustable Date Display Format Daylight Saving  | Protection) | 16 × 12 grids per channel  3 adjustable parameters for accurate detection Push Video / Push Status / FTP / E-Mail 2X digital zoom YES 4 inputs, 1 output YES YES (IR receiver built-in) YES 4 user levels for different access privilege YES Supports up to 25 letters Hue / Saturation / Contrast / Brightness YY/MM/DD, DD/MM/YY & MM/DD/YY   |  |
| Motion Detection Sen Event Notification Picture Zoom PTZ Control Alarm I/O RS485 IR Remote Control Key Lock (Password I User Level Video Loss Detection Camera Title Video Adjustable Date Display Format Daylight Saving Power Source (±10%)                      | Protection) | 16 × 12 grids per channel  3 adjustable parameters for accurate detection Push Video / Push Status / FTP / E-Mail  2X digital zoom YES  4 inputs, 1 output YES  YES (IR receiver built-in) YES  4 user levels for different access privilege YES Supports up to 25 letters Hue / Saturation / Contrast / Brightness YY/MM/DD, DD/MM/YY & MM/DD/YY YES   |  |
| Motion Detection Sen Event Notification Picture Zoom PTZ Control Alarm I/O RS485 IR Remote Control Key Lock (Password I User Level Video Loss Detection Camera Title Video Adjustable Date Display Format Daylight Saving Power Source (±10%) Operating Temperatur | Protection) | 16 × 12 grids per channel  3 adjustable parameters for accurate detection Push Video / Push Status / FTP / E-Mail  2X digital zoom YES  4 inputs, 1 output YES  YES (IR receiver built-in) YES  4 user levels for different access privilege YES  Supports up to 25 letters Hue / Saturation / Contrast / Brightness YY/MM/DD, DD/MM/YY & MM/DD/YY YES  DC12V / 3A  10°C ~ 40°C (50°F ~104°F) |  |
| Motion Detection Sen Event Notification Picture Zoom PTZ Control Alarm I/O RS485 IR Remote Control Key Lock (Password I User Level Video Loss Detection Camera Title Video Adjustable  | Protection) | 16 × 12 grids per channel  3 adjustable parameters for accurate detection Push Video / Push Status / FTP / E-Mail 2X digital zoom YES 4 inputs, 1 output YES YES (IR receiver built-in) YES 4 user levels for different access privilege YES Supports up to 25 letters Hue / Saturation / Contrast / Brightness YY/MM/DD, DD/MM/YY & MM/DD/YY YES DC12V / 3A                                  |  |



## SPECIFICATIONS

|   | 401122                |   |  |  |
|---|-----------------------|---|--|--|
| Ethernet National National                                | 10/100                | 10/100 Base-T. Supports remote control and live view via Ethernet |  |  |
| Network Protocol  |                       | TCP/IP, PPPOE, DHCP and DDNS                                      |  |  |
| ▼ Remote Surveillance from PC                             |                       |   |  |  |
| Compatible Operating System                               |                       | Windows & MAC   |  |  |
| Compatible Program  | Web Browser:          | Internet Explorer, Google Chrome & Safari                         |  |  |
|   | CMS Lite:             | 32CH central management software for Windows OS                   |  |  |
|   | QuickTime:            | For both Windows and MAC operating systems                        |  |  |
| Max. online users   | 20                    |   |  |  |
| Web Transmitting Compression Format                       |                       | H.264   |  |  |
| Network Live Audio  |                       | YES   |  |  |
| Remote Independent Operation                              | YES                   |   |  |  |
| Remote Event Download & Playback                          |                       | YES   |  |  |
| ▼ Mobile Surveillance                                     |                       |   |  |  |
| Арр   |                       | EagleEyes   |  |  |
| Compatible Devices  | iOS & Android devices |   |  |  |
| Push Video  | YES                   |   |  |  |
| Push Status   | YES                   |   |  |  |
|   |                       | TLO   |  |  |
| ▼ Others  |                       | 120   |  |  |
| ▼ Others EaZy Networking                                  |                       | YES   |  |  |
|   |                       |   |  |  |
| EaZy Networking   |                       | YES   |  |  |
| EaZy Networking<br>IVA                                    |                       | YES<br>YES  |  |  |
| EaZy Networking IVA DCCS Support                          | Live                  | YES<br>YES<br>YES   |  |  |
| EaZy Networking IVA DCCS Support AVTECH Free DDNS service | Live                  | YES YES YES YES   |  |  |

<sup>\*</sup> The specifications are subject to change without notice.

\*\* 1 HDD capacity up to 6TB

\*\*\* Dimensional tolerance: ±5mm

## REAR PANEL

