AVT208















8CH HD CCTV DVR

FEATURES

Free P2P Cloud EaZy Networking*

- Cloud EaZy Networking available to connect this device to Internet automatically in three steps with our free mobile app, EagleEyes.
- The "Buddy" feature to share the device access permission to other people.
- Device login / out notifications reported.



<u>Push Video & Push Status -</u> Active Event Notification with EagleEyes App

- Push Video to send instant notifications for an alarm event when an alarm device is connected to the DVR.
- Push Status to send instant notifications for system events, such as video loss or HDD data removal.



Intelligent Video Analysis

The Smart TVI DVR supports IVS (Intelligent Video System) to set a virtual detection line for people counting, virtual fence, and one-way pass. It's the advanced usage for motion detection to not only record but also summarize the detection data for further analysis.



HD Video Recording

- HD real-time recording brings users clear images while video recording and playback
- 1920*1080 Full HD video output service, giving the best image quality on LCD / LED monitors

Video Backup

Regular backup could be configured to automatically copy video footages to the specified location (USB drive or FTP) at the specified time.

External Disk Array Support for More Video Storage

eSATA interface built-in to connect a disk array (RAID 0 / 1 / 5 / 6 / 0 + 1 / 1 + 0) for more video storage.

Remote Surveillance

- Fully compatible with iOS and Android devices, and Internet Explorer on Windows operating system
- CMS Lite for 32 devices central management
- Applicable also to Apple's media player, QuickTime.



SPECIFICATIONS

Video System		NTSC / DAL (quite detection)	
Video System		NTSC / PAL (auto detection)	
Video Compression Format		H.264	
Video Input		8 channels (Composite video signal 1 Vp-p 75Ω BNC)	
Video Output	BNC VGA	YES	
	HDMI	YES	
		YES	
Record & Bac	kup		
Maximum Recording Rate 1080P 720P QHD Frame Field CIF		1920 x 1080 pixels with 120 IPS	
		1280 x 720 pixels with 240 IPS	
		960 x 540 pixels with 240 IPS	
		704×480 pixels with 240 IPS <ntsc> / 704×576 pixels with 200 IPS <pal:< td=""></pal:<></ntsc>	
		704x240 pixels with 240 IPS <ntsc> / 704×288 pixels with 200 IPS <pal></pal></ntsc>	
		352×240 pixels with 240 IPS <ntsc> / 352×288 pixels with 200 IPS <pal></pal></ntsc>	
Recording Mode		Manual / Timer / Motion / Alarm / Remote	
Pre-alarm Recording		YES	
Playback Channel		8CH	
Quick Search		Time / Motion / Alarm search mode	
Backup Device		USB 2.0 drive / Network	
Regular Backup		YES	
V Audio			
Audio Input		4 audio inputs	
Audio Output		2 Audio outputs (Mono)	
V General			
Hard Disk Storage**		Up to 3 SATA HDDs	
SATA Interface		YES	
eSATA Interface		YES (For external disk array connection)	
Image Quality Setting		SUPER BEST / BEST / HIGH / NORMAL	
USB Mouse Control		YES	
Motion Detection Area		16 × 12 grids per channel	
Motion Detection Sensitivity		3 adjustable parameters for accurate detection	
Event Notification		Push Video / Push Status / FTP / E-Mail	
Picture Zoom		2X digital zoom	
PTZ Control		YES	
Alarm I/O		8 inputs, 1 output	
RS485		YES	
IR Remote Control		YES (IR receiver built-in)	
Key Lock (Password Protection)		YES	
User Level		4 user levels for different access privilege	
Video Loss Detection		YES	
Camera Title		Supports up to 25 letters	
Video Adjustable		Hue / Saturation / Contrast / Brightness	
Date Display Format		YY/MM/DD, DD/MM/YY & MM/DD/YY	
Daylight Saving		YES	
Power Source (±10%)		DC19V / 3.42A	
Operating Temperature		10°C ~ 40°C (50°F~104°F)	
Operating Temperature Operating Humidity		10 C ~ 40 C (50 F ~ 104 F) 10% ~ 85%	
Dimensions (mm)***		430(W) × 65(H) × 338(D)	
Net Weight		700(VV) ~ 00(H) ~ 000(D)	

SPECIFICATIONS

Ethernet	Gigabit Base-T. Supports remote control and live view via Ethernet		
Network Protocol	TCP/IP, PPPOE, DHCP and DDNS		
▼ Remote Surveillance from PC		TOTAL THE CE, SITOL AND SITO	
Compatible Operating System	Windows & MAC		
Compatible Program	Web Browser:	Internet Explorer, Google Chrome & Safari	
	CMS Lite:	32CH central management software for Windows OS	
	QuickTime:	For both Windows and MAC operating systems	
Max. online users	20		
Web Transmitting Compression Format	H.264		
Network Live Audio	YES		
Remote Independent Operation	YES		
Remote Event Download & Playback	YES		
▼ Mobile Surveillance			
Арр	EagleEyes		
Compatible Devices	iOS & Android devices		
Push Video	YES		
Push Status	YES		
▼ Others			
EaZy Networking	YES		
IVA		YES	
DCCS Support	YES		
AVTECH Free DDNS service	YES		
Multiplex Operation	Live display / record / playback / backup / network operations		
System Recovery	System auto recovery after power failure		
Optional Peripherals	HDMI Matrix (HDM02)		

* The specifications are subject to change without notice.

** 1 HDD capacity up to 6TB

*** Dimensional tolerance: ±5mm

REAR PANEL

