



DGM1105



HD 1080P



PoE



DWDR




Mobile
Surveillance

2MP IR Bullet IP Camera

FEATURES

- **POE (Power-over-Ethernet)** support to eliminate the use of power cables and reduce installation costs
- **ONVIF** (**ONVIFS**) standard supported to simplify system integration
- **DWDR** to increase image recognizability in overexposure and dark areas
- **Waterproof** design on the Ethernet cable connector
- **Remote Surveillance**
 - **Fully compatible** with **iOS** and **Android** devices, and **Internet Explorer** on Windows operating system
 - Free PC program, **CMS Lite**, for 32CH devices monitoring on Windows operating system

DIMENSIONS



Dimensional tolerance: $\pm 5\text{mm}$



○ SPECIFICATIONS

■ Network		
LAN Port	YES	
LAN Speed	10/100 Based-T Ethernet	
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP, RTCP, IPv4, Bonjour, UPnP, DNS, UDP, IGMP, QoS, SNMP	
ONVIF Compatible	YES (Profile S)	
Number of Online Users	10	
Security	(1) Multiple user access levels with password (2) IP address filtering (3) Digest authentication	
Remote Access	(1) Internet Explorer on Windows operating system (2) CMS Lite, 32CH CMS software for Windows operating system (3) EagleEyes on iOS & Android mobile devices	
■ Video		
Network Compression	H.264 (Main Profile) / MJPEG	
Video Resolution	1920 x 1080 / 1280 x 720 / 720 x 480 / 352 x 240	
Frame Rate	30fps	
Multiple Video Streaming	2 (H.264, MJPEG)	
■ General		
Image Sensor	1/2.7" CMOS image sensor	
Min Illumination	0.1 Lux / F1.5, 0 Lux (IR LED ON)	
Shutter Speed	1/2 to 1/10,000 sec	
S/N Ratio	More than 48dB (AGC off)	
Lens	f3.8mm / F1.5	f3.6mm / F1.8
Viewing Angle	77° (Horizontal) / 45° (Vertical) / 88° (Diagonal)	96° (Horizontal) / 50° (Vertical) / 116° (Diagonal)
IR LED	2 Units	
IR Effective Distance**	Up to 25 meters	
IR Shift	YES	
White Balance	ATW	
AGC	Auto	
IRIS Mode	AES	
Sharpness	YES	
DWDR	YES	
POE	YES (IEEE 802.3af)	
Weather-proof	IP66	
Operating Temperature	-40°C ~ 50°C	
Operating Humidity	90 or less relative humidity	
Power Source (±10%)	12V / 1A	
Current Consumption (±10%)	150mA (IR OFF) / 400mA (IR ON)	
Power Consumption (±10%)	PoE & PoN: 6W; DC adapter: 4.8W	
Net Weight (kg)	0.36	



● SPECIFICATIONS (CONTINUED)

■ Others	
Mobile Surveillance	iOS & Android mobile devices
Motion Detection	YES
Event Notification	FTP / Email / SMS
RTC (real-time clock)	YES
Digital Pan / Tilt / Zoom	YES
Minimum Web Browsing Requirements	<ul style="list-style-type: none"> • Intel core i3 or higher, or equivalent AMD • 2GB RAM • AGP graphics card, Direct Draw, 32MB RAM • Windows 10, Windows 8, Windows 7, Windows Vista & Windows XP, DirectX 9.0 or later • Internet Explorer 7.x or later (Windows Edge not supported)

*The specifications are subject to change without notice.