## AVTECH

# **DGM5547T**
























#### 5MP H.265 IR Bullet IP Camera

#### **O** FEATURES

- Starlight visibility to offer clear & color images even at night
- Equipped with a motorized lens of f2.8 ~ 12mm
- MicroSD card support (up to 128GB) for video storage
- ONVIF (Onvirs) standard supported to simplify system integration
- POE (Power-over-Ethernet) support to eliminate the use of power cables and reduce installation costs
- Line in / out jacks available for audio transmission
- External Alarm I/O device connection
- IR effective range up to 40 meters for night surveillance
- WDR to increase image recognizability in overexposure and dark areas
- Remote Surveillance
  - -- Fully compatible with Internet Explorer 6 and above on Windows operating system

#### O DIMENSIONS



Dimensional tolerance: ± 5mm



### **O SPECIFICATIONS**

Image Sensor	1/2.8" SONY CMOS image sensor
Max. Resolution	2592 x 1944 (5MP)
Lens	Motorized f2.8 ~ 12mm / F1.6 ~ F2.2 (Auto Focus)
Viewing Angle	Wide: 105.41° (Horizontal) / 56.45° (Vertical) / 125.12° (Diagonal) Tele: 34.5° (Horizontal) / 19.5° (Vertical) / 39.5° (Diagonal)
Min Illumination	0.001 Lux / F1.6(Wide)~F2.2(Tele), 0 Lux (IR LED ON)
Shutter Speed	AES
IR LED	4 units
IR Effective Distance**	Up to 40 meters
Day / Night	YES
WDR Mode	WDR (120dB) / DWDR
RTC (real-time clock)	NTP / Manual
Micro SD Card Slot	YES (up to 128GB)
Video	
Compression	H.265 / H.264
Video Resolution	2592 x 1944 / 2560 x 1440 / 2048 x 1536 / 1080P / 720P / D1 / VGA / 640 x 360 / CIF
Frame Rate	25 IPS @ 2592 x 1922, 2560 x 1440 & 2048 x 1536 30 IPS @ 1920 x 1080, 1280 x 720, 640 x 480 & 320 x 240
Video Profile	High profile / Main profile / Baseline
Multiple Video Streaming	2 streams
S/N Ratio	More than 52dB (AGC off)
Image Mode	Normal / Super Starlight / Forced Frame Rate
Image Enhancement	WDR ( Level 0 ~ 255) / DWDR / BLC / HLC / 2D DNR / 3D DNR
Day / Night Switch	Auto / Schedule / Manual
Forced Anti-flicker	YES
Defog	YES
White Balance	AWB
Image Orientation	Flip / Mirror
Privacy Mask	4 customized areas
Text Overlay	YES
OSD Title	Location / font size / text configurable; English & Chinese characters supported
Image Mode	Normal / Super Starlight / Forced Frame Rate
Audio	
Line in	YES
Line out	YES
Encoding	G711 / G711A / AAC
Audio Adjustment	Input & Output
Alarm & Event	
Alarm in	YES
Alarm out	YES
Detection Mode	Human (Day & Night) / Motion
Detection Schedule	YES
Motion Detection Area	1x1, 2x2, 3x3, 3x4, 4x4, 8x8, 16x16, 22x18
Human Detection Alert	Audio alert with customized mp3 audio file(s)



## • SPECIFICATIONS (CONTINUED)

On-Board Storage	Built-in memory card slot, supports microSD / SDHC / SDXC card up to 128GB
Overwrite	YES
Maximum Recoding Time / per File	2, 5, 10, 20 & 30 minutes configurable
Recording Schedule	YES
Network	
LAN Port	RJ45 connector x 1
LAN Speed	10/100 Based-T Ethernet
Supported Protocols	TCP/IP, ICMP, HTTP, DHCP, DNS, RTP, RTSP, NTP, IPv4, IPv6, HTML5, ONVIF
ONVIF Compatible	YES (Profile S)
Number of Online Users	6
Security	<ul><li>(1) Up to 10 user accounts with different access levels and passwords</li><li>(2) IP address filtering</li><li>(3) Digest authentication</li></ul>
Remote Access	Internet Explorer 6 and above
General	
Web Interface Language	English, Korea, Traditional Chinese, Simplified Chinese, Turkish, Italian, German, Russian & Croatian
Operating Temperature	-30°C ~50°C
Operating Humidity	30% ~ 90%
POE	YES (IEEE 802.3af)
Power Source (±10%)	PoE (IEEE 802.3af) / DC12V
Power Consumption (±10%)	PoE: 7.5W; DC adapter: 6W
Net Weight (kg)	0.67
Certification	CE / FCC
Casing	IP67
Minimum Web Browsing Requirements	<ul> <li>Intel core i3 or higher, or equivalent AMD</li> <li>2GB RAM</li> <li>AGP graphics card, Direct Draw, 32MB RAM</li> <li>Windows 10, Windows 8, Windows 7, DirectX 9.0 or later</li> </ul>

<sup>.\*</sup>The specifications are subject to change without notice.