



IR DOME IP CAMERA SERIES

OPERATION GUIDE

Please read instructions thoroughly before operation and retain it for future reference.

IMPORTANT SAFEGUARD



All lead-free products offered by the company comply with the requirements of the European law on the Restriction of Hazardous Substances (RoHS) directive, which means our manufacture processes and products are strictly "lead-free" and without the hazardous substances cited in the directive.



The crossed-out wheeled bin mark symbolizes that within the European Union the product must be collected separately at the product end-of-life. This applies to your product and any peripherals marked with this symbol. Do not dispose of these products as unsorted municipal waste. Contact your local dealer for procedures for recycling this equipment.



This is a class A product. In a domestic environment this product may cause radio interference in which case the user may be required to take adequate measures.

Federal Communications Commission Interference Statement

This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device mat not cause harmful interference, and
- (2) This device must accept any interference received, including interference that may cause undesired operation.

Trademark Acknowledgements

iPad® & iPhone® are the registered trademarks of Apple Inc.

Android™ is a trademark of Google Inc. Use of this trademark is subject to Google Permissions.

Microsoft®, Windows® & Internet Explorer® are registered trademarks of Microsoft Corporation in the United States and/or other countries.

Disclaimer

We reserve the right to revise or remove any content in this manual at any time. We do not warrant or assume any legal liability or responsibility for the accuracy, completeness, or usefulness of this manual. The content of this manual is subject to change without notice.

This product doesn't have a standby / off mode.

MPEG4 Licensing

THIS PRODUCT IS LICENSED UNDER THE MPEG4 VISUAL PATENT PORTFOLIO LICENSE FOR THE PERSONAL AND NON-COMMERCIAL USE OF A CONSUMER FOR (i) ENCODING VIDEO IN COMPLIANCE WITH THE MPEG4 VISUAL STANDARD ("MPEG-4 VIDEO") AND/OR (ii) DECODING MPEG4 VIDEO THAT WAS ENCODED BY A CONSUMER ENGAGED IN A PERSONAL AND NON-COMMERCIAL ACTIVITY AND/OR WAS OBTAINED FROM A VIDEO PROVIDER LICENSED BY MPEG LA TO PROVIDE MPEG4 VIDEO. NO LICENSE IS GRANTED OR SHALL BE IMPLIED FOR ANY OTHER USE. ADDITIONAL INFORMATION INCLUDING THAT RELATING TO PROMOTIONAL INTERNAL AND COMMERCIAL USES AND LICENSING MAY BE OBTAINED FROM MPEG LA, LLC. SEE [HTTP://WWW.MPEGLA.COM](http://WWW.MPEGLA.COM).

GPL Licensing



This product contains codes which are developed by Third-Party-Companies and which are subject to the GNU General Public License ("GPL") or the GNU Lesser Public License ("LGPL").

The GPL Code used in this product is released without warranty and is subject to the copyright of the corresponding author.

Further source codes which are subject to the GPL-licenses are available upon request.

We are pleased to provide our modifications to the Linux Kernel, as well as a few new commands, and some tools to get you into the code. The codes are provided on the FTP site, and please download them from the following site or you can refer to your distributor:
<http://download.dvrtw.com.tw/GPL/IPCAM/A-Seriers/linux.tar.gz>

TABLE OF CONTENTS

1. OVERVIEW.....	1
1.1 Product Features.....	1
1.2 Package Content.....	1
1.3 Product Overview.....	1
1.4 Connectors	2
1.5 External Alarm Connection.....	2
1.6 Status Indicator (<i>For Type 1 only</i>)	2
1.7 Insert a Micro SD card.....	3
2. CAMERA ACCESS WITH INTERNET EXPLORER.....	4
2.1 Camera Login.....	4
2.2 Control Panel Overview	4
2.3 Digital PTZ (DPTZ) Operations	6
2.4 Event Record Search & Playback	6
3. CAMERA CONFIGURATIONS.....	8
3.1 System configuration menu.....	8
3.2 Network	9
3.2.1 Network	9
3.2.2 QoS	9
3.2.3 DDNS	9
3.2.4 SNTP	9
3.2.5 FTP.....	10
3.2.6 MAIL	10
3.2.7 SMS.....	11
3.2.8 Filter	11
3.2.9 UPnP / Bonjour.....	12
3.2.10 RTP	13
3.3 Camera	13
3.3.1 Camera.....	13
3.3.2 Video	14
3.3.3 Color.....	14
3.3.4 Audio (<i>For selected models only</i>)	14
3.3.5 Advanced.....	15
3.4 Record.....	15
3.4.1 Record.....	15
3.4.2 Record Timer.....	16
3.5 Storage.....	16
3.5.1 Memory	16
3.6 Trigger	17
3.6.1 Trigger	17
3.7 General	18
3.7.1 General.....	18
3.7.2 Time.....	19
3.7.3 Server Log	19
3.7.4 Online	20
3.7.5 Account.....	20
3.7.6 Google Maps	21
3.7.7 Maintenance.....	21
APPENDIX 1 PRODUCT SPECIFICATIONS.....	23
APPENDIX 2 BIT RATE TABLE FOR REFERENCE	25
APPENDIX 3 API ID APPLICATION FOR SMS MESSAGING.....	27
APPENDIX 4 Q&A	29
APPENDIX 5 RECORDING TIME TABLE	30
APPENDIX 6 MICRO SD CARD COMPATIBLE LIST.....	31

1. OVERVIEW

1.1 Product Features

- Worked with **PoC (Power-over-Coaxial) converter** to set up the whole HD IP system with coaxial cables, suitable for **replacing your existing CCTV system to HD IP system** effectively
- **Quick network setup** with your iOS® / Android™ mobile device
- **External alarm I/O device connection**
 - For more accurate detection
 - Possible to enable active event notifications to your iOS® & Android™ mobile devices (**Push Video**) when used with **Push Video NVR series**
- **ONVIF** standard supported to simplify system integration
- **3-axis mechanism** for flexible ceiling and wall-mount installation
- MicroSD card support for **video storage**
- **(For selected models only) WDR** to increase image recognizability in overexposure and dark areas
- **Remote Surveillance**
 - Fully compatibility on **iPhone & iPad**, and **Internet Explorer®** on Windows® operating system

1.2 Package Content

IP camera


Screws & Wall Plugs

Quick Setup


1.3 Product Overview

■ Type 1


Camera Overview



Side View



■ Type 2



1.4 Connectors


Power cable	DC12V power supply.
Coaxial cable	Connect to our PoC converter with a BNC connector for video transmission.
RESET	With the power connected, press to reset all parameters, including the IP address to factory default settings. The camera will reboot after default reset. Please do not disconnect your camera during the reset process.
Alarm in / Alarm out	For external alarm device connection, please refer to “* For selected models only 1.5 External Alarm Connection” at page 2.
Line in (Blue) / Line out (Green)*	Support speaker and microphone connection.

* For selected models only

1.5 External Alarm Connection

This camera supports external I/O device connection for easy connection.

Below shows you how to connect an external device to this camera.



1.6 Status Indicator (For Type 1 only)

ICON	LAN connection status	Internet connection status
System Status		
During powering on	Always on	Always on
Reset default	Blinking (on 250 ms, off 250 ms) ●○●○●○●○●○	Always off
Upgrade	Blinking (on 250 ms, off 250 ms) ●○●○●○●○●○	Blinking (on 250 ms, off 250 ms) ●○●○●○●○●○
Connection Status		
LAN connected	Always on	--
LAN disconnected	Blinking (on 100 ms, off 500 ms) ●○○●○○●○○	--
Internet connected	--	Always on
Internet disconnected	--	Blinking (on 100 ms, off 500 ms) ●○○●○○●○○
3G Connection Error on iPhone / iPad / Android Mobile Device		
3G Connection Setting Uncompleted	--	Blinking (on 5 sec, off 0.5 sec, on 0.5 sec, off 0.5 sec, on 5 sec) ●●●●○●○●●●●

* LED blinking frequency - ● LED on / ○ LED off


1.7 Insert a Micro SD card

For local video recording, a micro SD card slot can be found on the camera. The camera doesn't support hot-swapping. Please insert or remove the micro SD card with power disconnected. Please follow the directions in the below graphic to insert Micro SD card properly:

■ Type 1



■ Type 2



Note: Before inserting a micro SD card, make sure you've copied all important data saved in the card (if any) to other storage media, or all data will be removed after inserting it to the camera.

Note: For the compatible list of the micro SD card, please refer to "APPENDIX 6 MICRO SD CARD COMPATIBLE LIST" at page 31.

2. CAMERA ACCESS WITH INTERNET EXPLORER

This camera can be accessed via Microsoft® Internet Explorer®, and iOS® / Android™ mobile devices with our self-developed program “EagleEyes” installed depending on different using situations.

Note: For details about accessing this camera via iOS® / Android™ mobile devices, please refer to <http://www.eagleeyescctv.com>.

Before using the camera, make sure you have configured the network settings, and the network connection is fine.

- For network configurations, please refer to “**Advanced Network Setup**” downloadable from www.surveillance-download.com/user/p521.swf.

2.1 Camera Login

Step1: Open your web browser, and key in <http://ipaddress:portnum> in the URL address box.

For example, for the IP address 60.121.46.236 and port No. 888, please key in “<http://60.121.46.236:888>” into the URL address box, and press “Enter”.

Step2: In the login page, key in the user name and password, and enter the security code from the image below if any. Then, click “LOGIN”.

Step3: The wizard is then started.


- To skip the wizard and directly access the camera live view, click “Close”.
- To directly access the camera live view without starting the wizard for the login next time, check “Do not start wizard at login”.

Note: If you’re prompted to install “VLC player”, “Software” or “H264 Streaming Viewer”, please agree to proceed the installation. Or, you might not be able to see the live view properly.

Step5: When the login is successful, the live view is shown.

2.2 Control Panel Overview

Note: The buttons available depend on the camera model you have, and the user level used to log in.



Function	Icon	User Level	Description
Live		Supervisor / Power User / Normal User / Guest	Switch to the live view page.
Backup		Supervisor / Power User	Enter the event record list for video playback. For details, please refer to "2.4 Event Record Search & Playback" at page 6.
DPTZ		Supervisor / Power User / Normal User	Switch to the DPTZ configuration page. For details, please refer to "2.3 Digital PTZ (DPTZ) Operations" at page 6.
Config.		Supervisor	Switch to the system configuration page, and the functions available for "Supervisor" and "Power User" are different. For details, please refer to "3.1 System configuration menu" at page 8.
Live player	--	Supervisor / Power User / Normal User / Guest	Select the image player from the drop-down list: <ul style="list-style-type: none"> ■ ActiveX ■ QuickTime <p>QuickTime is Apple Inc.'s multimedia software. You need to have QuickTime installed in your operating system before selecting "QuickTime". When it is selected, you will be prompted to enter the user name and password to access the camera.</p> <ul style="list-style-type: none"> ■ VLC
Quality	--	Supervisor / Power User / Normal User	Click & drag the slider to select the video quality: Basic / Normal / High / Best.
Video Profile	--	Supervisor / Power User / Normal User	Select the image profile from the drop list: <ul style="list-style-type: none"> ■ 1920 x 1080 ■ 1280 x 720 ■ 720 x 480 ■ 352 x 240 <p><i>The profile could be changed from "Config" → "Camera" → "Video".</i></p>
Full Screen		Supervisor / Power User / Normal User	Click to display the image in full screen. To exit the full screen mode, press "Esc" on your keyboard.
Snapshot		Supervisor / Power User / Normal User	Click to take a snapshot of the current view on a new window. Right click on the picture and re-save it to the location you want.
Live View Size:		Supervisor / Power User / Normal User	
Normal Size			The current live view size is the same as the selected resolution.
Fit to screen			The selected resolution is resized to fit into the current live view size. <i>This icon doesn't work when the selected resolution is VGA or QVGA.</i>
Scale*			Click and hold the movable square on the left bottom corner of the live view to move <i>This icon appears only when the selected resolution is larger than the current live view size.</i>
Double Size			The QVGA resolution is resized to fit into the current live view size. <i>This icon appears only when the selected resolution is QVGA (320 x 240) or CIF (352 x 240).</i>
Audio On / Off*	/	Supervisor / Power User / Normal User	Click to switch the audio-in on / off.
Microphone*	/	Supervisor	Click to switch the audio-out on / off.
Manual Alarm Out		Supervisor / Power User / Normal User	Click to force the connected alarm-out device to work. For example, when your alarm device is a buzzer, click this button and your buzzer will start to sound even if there's no alarm event.
DPTZ*		Supervisor / Power User / Normal User	Click to enable digital PTZ functions with zoom-in ratio up to 16X.
Focus Assist*		Supervisor / Power User / Normal User	Click to help you determine whether the image clearness is adjusted well when you're adjusting your camera focus. Two values will be calculated and shown as "XX / YY". <ul style="list-style-type: none"> ■ YY is the best focus value for your current camera view ■ XX is your current focus value <p>When XX is closer to YY, the clearer and sharper images you'll get for your camera view.</p>

* Selected models only

2.3 Digital PTZ (DPTZ) Operations

This camera has PTZ capability, i.e. digital PTZ (hereafter called “DPTZ”), for wide area monitoring.

STEP1: Click “DPTZ” to show the DPTZ control panel.




FUNCTION	ICON	DESCRIPTION
Moving panel	--	When is selected, the moving control panel will be shown to move the picture after zoom-in is performed.
Take snapshots		Click to take a snapshot of the current view on a new window. Right click on the picture and re-save it to the location you want.
Zoom in / out	/	Click once to enlarge the picture by 1X, and click once to restore the zoom ratio by 1X.
Max. zoom in / out	/	Click once to enlarge the picture to the max zoom ratio by 16X, and click once to restore the picture ratio to 1X.

2.4 Event Record Search & Playback

Note: To save more recorded data, it's recommended to use this camera with the compatible NVR.

Note: The alarm type available depends on the model you have.



	Previous / Next Hour	Click to jump to the next / previous time interval in an hour, for example, 11:00 ~ 12:00 or 14:00 ~ 15:00, and start playing the earliest event video clip recorded during this whole hour.
	Fast Forward	Increase the speed for fast forward. Click to get 2X, 4X, 8X & 16X speed forward eventually.
	Fast Rewind	Increase the speed for fast rewind. Click to get 2X, 4X, 8X & 16X speed rewind eventually.
	Play	Click to play the current video clip.
	Pause	Click to pause the video playback.
	Stop	Click to stop the video playback.
	Step	In the pause mode, click to get one frame forward.
	Audio	Click to mute the playback if necessary, and click again to restore. <i>This function is available only when a speaker is connected during recording.</i>
	Download	Click to download the current video clip to the specified path in your PC. <i>The downloaded video can only be opened by our own video player. Please go to "General" → "Maintenance" to download the video player, or get the player from the CD supplied with the sales package.</i>

3. CAMERA CONFIGURATIONS

Users can further configure this network camera by accessing via Internet Explorer.

3.1 System configuration menu

Click "Config." to enter the configuration page.

The functions are categorized into six menus: Network, Camera, Record Timer, Storage, Trigger and General.

- For details about "Network", please refer to "3.2 Network" at page 8.
- For details about "Camera", please refer to "3.3 Camera" at page 13.
- For details about "Record", please refer to "3.4 Record" at page 15.
- For details about "Storage", please refer to "3.5 Storage" at page 16.
- For details about "Trigger", please refer to "3.6 Trigger" at page 17.
- For details about "General", please refer to "3.7 General" at page 18.

Main Menu	Sub-Menu	Reference
Network	Network	Configure network settings.
	QoS	Limit the data flow for live streaming.
	DDNS	Enter DDNS information when the network type is PPPOE or DHCP.
	SNTP	Synchronize your camera time with the networked computer systems.
	FTP	Enter the FTP information for event notifications when "FTP" is chosen in "Trigger" → "Trigger".
	Mail	Enter Email information for event notifications when "Email" is chosen in "Trigger" → "Trigger".
	SMS	Enter text messaging information for SMS notifications when "SMS" is chosen in "Trigger" → "Trigger".
	Filter	Choose to permit or block the IP address(es) which can access this camera.
	UPnP	<i>*Suitable for Windows-based operating system.</i> Allow this camera to be detected among devices within the same network area for easy and quick usage.
	Bonjour	<i>*Suitable for Apple Mac-based operating system.</i> Allow this camera to be detected among devices within the same network area for easy and quick usage.
	RTP	Set the parameters for video data transmission when you're using multimedia other than web browsers and Video Viewer for remote access.
Camera	Camera	1. Rename the camera. 2. Change the place where the camera name is shown on the screen. 3. Specify where to save the snapshot pictures.
	Video	Adjust video-related settings in different video format.
	Color	Adjust the color performance.
	Audio*	Adjust the audio volume of the microphone and speaker.
	Advanced	Adjust the camera parameters if necessary.
Record	Record	Configure the record function.
	Record Timer	Schedule external alarm recording.
Storage	Memory	Check the current storage capacity and clear all recorded data when needed.
Trigger	Trigger	1. Enable / disable motion, alarm and PIR detection. 2. Set the motion detection area. 3. Configure how the camera reacts for any event.
General	General	1. Select the language of the web browser. 2. Check the MAC address of the camera. 3. Lock camera access after the specified time. 4. Enable or disable LED status indication.*
	Time	Set daylight saving time and the current time.
	Server Log	Check the system event logs.
	Online	Check the current online user(s).
	Account	1. Create a new user account with different access privilege. 2. Modify or delete an existing user account.
	Google Maps	Allow you to know where the network camera is.
	Maintenance	1. Check the current firmware version and upgrade your camera. 2. Copy system configurations. 3. Reboot the camera. 4. Download the video player to play the recorded data.

*Selected models only

3.2 Network

3.2.1 Network

You can set the network configuration of the network camera depending on your network type.

For details, please refer to “Advanced Network Setup” from www.surveillance-download.com/user/p521.swf.

The screenshot shows the 'Network Configuration' section of the camera's web interface. It includes fields for Server IP (192.168.1.10), Gateway (192.168.1.1), Net Mask (255.255.255.0), Port (80), DNS1 (168.95.1.1), DNS2 (139.175.55.244), and MAC Address (00:0E:53:20:E7:3E). There are 'Save' and 'Reload' buttons at the bottom.

3.2.2 QoS

QoS, Quality of Service, is the ability to control the data flow for real-time streaming. This function is important if your network bandwidth is insufficient and you have other devices to share the network bandwidth.

Check “QoS Enable”, and set the max. upload rate from 256 to 10240 kbps.

The screenshot shows the 'QoS Configuration' section. It has a radio button for 'Enable' (selected) and 'Disable'. The 'Interface' dropdown is set to 'Ethernet'. The 'Max. Upload Rate' field contains '4096' kbps. There are 'Save' and 'Reload' buttons at the bottom.

3.2.3 DDNS

Select “On” when the selected network type in “Network” is “PPPOE” or “DHCP”.

For details, please refer to “Advanced Network Setup” from www.surveillance-download.com/user/p521.swf.

The screenshot shows the 'DDNS Configuration' section. It has a radio button for 'Enable' (selected) and 'Disable'. The 'System Name' dropdown is set to 'eagleeyes'. The 'Hostname' dropdown is set to 'MAC000E5320E73E.ddns.eagleeyes.tw'. There are 'Save' and 'Reload' buttons at the bottom.

3.2.4 SNTP

SNTP (Simple Network Time Protocol) is used to synchronize your camera time with the networked computer systems.

The screenshot shows the 'SNTP Configuration' section. It includes fields for 'GMT' (set to '(GMT+08:00) Taipei'), 'NTP Server' (set to 'tock.stdtime.gov.tw'), 'Sync. Period' (set to 'Daily'), and 'Server Time' (showing '2011-08-30 20:34:42'). A 'Sync.' button is at the bottom, followed by 'Save' and 'Reload' buttons.

Function	Description
GMT	Once users choose the time zone, the network camera will adjust the local area time of the system automatically.
NTP Server	Simply use the default SNTP server (For example, tock.stdtime.gov.tw) or change to another server with which users are familiar.
Sync. Period	Select “Daily” to synchronize the camera time with the network time every day or “None” to turn off this function.
Sync	Click and the network camera will synchronize the time with the network time.

3.2.5 FTP

Enter the detailed FTP information and click “Save” to confirm. The information you set here will be applied when “FTP” is selected in “Trigger” → “Trigger”.

The screenshot shows the 'FTP Configuration' section of a web-based configuration tool. It contains five input fields: 'Username' (manager), 'Password' (redacted), 'Server' (321.382.12.99), 'Port' (21), and 'Directory' (upload). Below the fields are three buttons: 'Save' (blue), 'Test' (green), and 'Reload' (blue).

3.2.6 MAIL

Enter the detailed e-mail information and click “Save” to confirm. The information you set here will be applied when “Email” is selected in “Trigger” → “Trigger”.

The screenshot shows the 'Mail' configuration interface. It includes two main sections: 'SMTP Configuration' and 'E-Mail Address List'. In the 'SMTP Configuration' section, fields are filled with: 'SMTP Server' (smtp.gmail.com), 'Port' (465), 'Mail From' (manager), 'SSL Encryption' (Yes), 'Verify Password' (Yes), 'Username' (manager), 'Password' (redacted), and 'Subject' (Trigger Occur!). Below these are three buttons: 'Save' (blue), 'Test' (green), and 'Reload' (blue). The 'E-Mail Address List' section has a header with 'Add' (green), 'Edit' (yellow), and 'Delete' (red) buttons, followed by a table with columns 'Receiver Name' and 'E-Mail Address'.

Function	Description
SMTP Server	Enter the SMTP server address provided from your e-mail system supplier.
Port	Enter the port number provided from your e-mail system supplier. If this column is left blank, the e-mail server will use port 25 to send e-mails.
Mail From	Enter the name of the sender.
SSL Encryption	Select “Yes” if your e-mail server is using SSL encryption to protect your e-mail content from unauthorized access.
Verify Password	Some mail servers are required to verify the password. Please enter the “user name” and “password”.
Subject	Enter the subject of the notifying email you want to see when the camera is triggered.
E-Mail Address List	Add the e-mail address(s) of the assigned recipient(s).
Test	When all information is entered, click “Test Mail” to try if the receipt.

3.2.7 SMS

Note: Before using this function, you need to apply an account and get an API ID from the mobile messaging company, such as Clickatell and EVERY8D. For details, please refer to "APPENDIX 3 API ID APPLICATION FOR SMS MESSAGING" at page 27.

Enter the detailed information needed for text messaging, and click "Save" to confirm. The information you set here will be applied when "SMS" is selected in "General" → "Trigger".

The screenshot shows the "SMS Configuration" section of a web-based camera control interface. It includes fields for System (clickatell), Username (tech), Password (*****), API ID (3281378), Recipient (+886912665475), Transfer Interval (15), and a message content area containing "[192.168.1.10] unauthorized access!". There are also buttons for Save, Test, and Reload.

Function	Description
System	The text messaging service provider is Clickatell.
User name / Password	Enter the account user name and password you created in Clickatell.
API ID	Enter the API ID you applied from Clickatell.
Recipient	Click "Add" to enter the phone number, including the country code, to receive the text message. Five sets of phone numbers are allowed.
Transfer Interval	Set the interval time in minutes between two-message sending. The options are 0, 15, 30 & 60.
Reset Counter	Click to restart the text messaging, and the SMS will be sent after the specified time interval since you click this button.
Message	Enter the text content (up to 70 characters) you want to send with the text message.
Test	To know whether your SMS setting is correct, click this button to immediately send a SMS to your phone. Note: This testing is not free and you will be charged for SMS sending base on your local rate.

3.2.8 Filter

Choose to permit or block the IP address(es) which can access this camera, and click "Save" to confirm.

The screenshot shows the "Filter Configuration" section. It includes fields for Error Count (3), Error Lock Time (1), Echo Request (Non-Block selected), and sections for IP/MAC Filter Configuration (Enable selected) and IP/MAC Filter Rules (Allow selected). A table lists a rule for IP 192.168.1.122. There are buttons for Save and Reload.

Function	Description
■ Filter Configuration	
Error Count	Set the maximum count for login failure. When the maximum count is reached, the IP address trying to access the network camera will be locked.
Error Lock Time	Set the lock time in minutes when the maximum count of error login for an IP address is reached.
Echo Request	Select “Non-Block” to allow other users to use the ping command to detect the IP address of your network camera, or “Block” to deny the ping command request.
■ IP/MAC Filter Configuration	
IP/MAC Filter	Choose to enable or disable the filter function.
IP/MAC Filter Policy	If “Enable” is selected, choose whether you want to permit (Allow) or block (Deny) the IP address list below.
■ IP/MAC Filter Rules	
Rule	<ul style="list-style-type: none"> To add an item to the IP address list, key in the IP address in “Rule”, and click “Add”. To remove an existing item in the IP address list, click the item you want to remove, and click “Delete”.

3.2.9 UPnP / Bonjour

“UPnP” stands for “Universal Plug and Play”, which allows devices to connect seamlessly in the home and corporate environments and simplify installation of computer components, and is only suitable for Microsoft Windows-based operating system.

“Bonjour” functions the same as “UPnP”, but it’s only suitable for Apple Mac-based operating system.

➤ UPnP

UPnP Configuration

UPnP: Enable Disable

Friendly Name: IP CAMERA (Fixed) 000E531574E3

➤ Bonjour

Bonjour Configuration

Bonjour: Enable Disable

Device Name: IP CAMERA (Fixed) AVN806-000E5320E73E

Check “Enable” to allow the network camera to be detected among devices within the same network area, and set the identification name of the camera in “Friendly name”.

When this function is activated, the other PC within the same domain as this camera will be able to search this camera in:

- “Network Neighbor” with the identification name set in “Friendly name” for Windows-based PC, or
- “Finder” (finder) or “Bookmark” with the identification name set in “Device Name” for Mac-based PC.

Double-click it to quickly open the web browser for camera access.

Port Mapping (Available only in UPnP)

This function can eliminate the need to additionally access the router for port forwarding.

For details, please refer to “Advanced Network Setup” from www.surveillance-download.com/user/p521.swf

Note: Before using this function, make sure your router supports UPnP, and this function is enabled. If not, please access your router additionally for port forwarding.

When “Port Mapping” is set to “Enable”, the system will automatically assign an IP address or port number for you if no IP address or port number is entered.

Port Mapping Configuration

Port Mapping: Enable Disable

Router IP: (LAN IP Address)

HTTP Port: 0

*If the value is set to blank or 0, a port number will be assigned automatically upon function activation.

Note: When the configurations are saved successfully, you'll see a message indicating the IP address and port number assigned to this network camera.

3.2.10 RTP

The Real-time Transport Protocol (RTP) is an Internet protocol standard to manage the real-time transmission of multimedia, such as VLC player.

The media player you want to use for remote access must support RTP transmission for this function to work normally.

Note: When you're about to end the remote access, please press the stop button on your media player first, and then close the program. This is to ensure the server receives the stop command, and also help to protect the server from redundant data transmission.

Port Range			
Start Port:	50000	End Port:	60000
Video			
Profile	Address	Port	Time to Live (TTL)
1	239.101.101.101	9000	15
2	239.101.101.102	9000	15
3	239.101.101.103	9000	15
4	239.101.101.104	9000	15
Audio			
Profile	Address	Port	Time to Live (TTL)
1	239.101.102.101	9000	15
2	239.101.102.102	9000	15
3	239.101.102.103	9000	15
4	239.101.102.104	9000	15

Function	Description
■ Port Range	
The port range used by RTP is limited, and preserving 100 ports between the start port and end port is necessary.	
Start Port	The range of the start port is 1024 ~ 65434.
End Port	The range of the end port is 1124 ~ 65534.
■ Video	
Address and port for video transmission	Set a specific address and port for multicast of profile 1 ~ 4. The range of the address is limited between 224.0.0.1 ~ 239.255.255.255. The port for multicast must be an even number.
■ Audio	
Address and port for audio transmission	Set a specific address and port for multicast of audio. The range of the address is limited between 224.0.0.1 ~ 239.255.255.255. The port for multicast must be an even number.

3.3 Camera

3.3.1 Camera

Rename the camera, and change the place where the camera name is shown on the screen, UP-LEFT / UP-RIGHT / DOWN-LEFT / DOWN-RIGHT. "Snapshot Path" is used to specify the path to save snapshot files.

Camera Configuration	
Title:	IPCAM
Position:	DOWN-RIGHT
Snapshot Path:	C:\
Save	Reload

3.3.2 Video

Adjust video-related settings in different video format.

- “Quality” is related to image clearness.
- “FPS” is related to the fluency of the video. The more the FPS, the more fluent the video.
- “Max Bit Rate” is the maximum limitation of data transmission in the selected image format and resolution.

Note: QQVGA is for mobile surveillance only.

Video Configuration

Configuration

Power Line Frequency: 60 Hz

Profile

Profile	Media Type	Resolution	Quality	FPS	Max Bit Rate
1	H264	1920x1080	BEST	30	8000
2	H264	720x480	HIGH	30	5000
3	H264	352x240	HIGH	30	5000
4	JPEG	352x240	HIGH	30	5000

Save **Reload**

3.3.3 Color

Adjust the color performance from Brightness, Contrast, Hue and Saturation. Click and drag the slider to preview the color change on the right side of the page and adjust the image color.

To restore the default values, click “Back to Default”

Color Configuration

Brightness: 50
Contrast: 55
Hue: 50
Saturation: 65

Live View



Back to Default **Reload**

3.3.4 Audio *(For selected models only)*

Drag the slider to adjust the volume of the microphone and speaker.

Audio Volume Configuration


Input(Mic.): 5 Mute
Output(Speaker): 5 Mute

Back to Default **Reload**

3.3.5 Advanced

Adjust the camera parameters if necessary.

Note: The functions available depend on the model number used.



Item	Description
Fixed Shutter	Shutter Speed is a function that can adjust the duration of the electronic shutter to produce optimum image quality. Select the shutter speed suitable for your environment.
Shutter Speed	Select the shutter speed suitable for your environment. A slower shutter speed in dark conditions will help to produce a brighter image, but will produce fewer frames per second, which may cause images to get blurry during motion. <ul style="list-style-type: none">● When "Auto" is selected, the iris mode is "AES".● When a certain speed is selected, the iris mode is switched to "AI", and the image brightness is available to adjust from "IRIS".
Exposure Control	This function is used to synchronize the shutter time to the fluorescent light to suppress image flickering.
Exposure Value	Drag the slider to adjust the exposure level from 0 ~ 4.
Mirror	Select "ON" to rotate the images horizontally based on your installation situation when necessary.
Flip	Select "ON" to rotate the image 180° when necessary.
IR Control	Select "Auto" to automatically enable IR LEDs at night or in the dark environment, "On" to always enable IR LEDs, or "OFF" to disable this function.
IR Enhanced	Select "On" to enhance IR LEDs performance.
IR Turn On Level	Select the level for IR light to activate.
White Balance	Process the current image to retain color balance over a color temperature range. The options are: Auto, 2500K, 3200K, 4200K, 5800K, 9500K.
Sharpness	Sharpness enhances the clarity of image detail by adjusting the aperture and sharpening the edges in the pictures. Hold and drag the slider to adjust the level of sharpness from 0 ~ 100. The higher the value, the sharper the image.
Wide Dynamic Range*	Wide Dynamic Range (WDR) is used when users need to increase image recognizability in overexposure and dark areas. The options are: LOW / MIDDLE / HIGH / OFF

3.4 Record

3.4.1 Record

In "Record Configuration", you can:

- Enable or disable the alarm record function. When "Enable" is set to "No", the alarm record function is disabled even if you enable it in other configuration pages.
- Select if the data should be overwritten when the memory storage is full.
- Enable or disable the audio record function.

Note: Audio recording is available for selected models only.

- Select the video resolution for event recording.

Note: The higher resolution you choose, the more accuracy and higher image quality the recording will be, but the faster the memory storage is consumed and become full

Record Configuration

Enable: Yes No

Overwrite: Yes No

Audio Record: Yes No

Profile: Profile2 720x480

3.4.2 Record Timer

To schedule alarm recording, enable it, and select the day and time for recording.

Note: Internal alarm is available for selected models only.

Note: The timer must be enabled for the record function to work properly.

External Alarm Internal Alarm

Enable: Yes No

	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23
SUN	<input checked="" type="checkbox"/>																							
MON	<input checked="" type="checkbox"/>																							
TUE	<input checked="" type="checkbox"/>																							
WED	<input checked="" type="checkbox"/>																							
THU	<input checked="" type="checkbox"/>																							
FRI	<input checked="" type="checkbox"/>																							
SAT	<input checked="" type="checkbox"/>																							

3.5 Storage

3.5.1 Memory

In "Memory", you can check the remaining capacity for recording, or clear all recorded data saved if needed.

Note: The recorded data will be removed also when you reset or reboot this camera.

Note: To know how and where to insert a micro SD card, please refer to "1.7 Insert a Micro SD card" at page 3. To know the compatible list of micro SD cards, please refer to "APPENDIX 6 MICRO SD CARD COMPATIBLE LIST" at page 31.

Note: To save more recorded data, it's recommended to use this camera with the compatible NVR.

Note: To know the total recording time per recording resolution, please refer to "APPENDIX 5 RECORDING TIME TABLE" at page 30.

Memory Configuration

File System: RAMDISK

Capacity Total: 20.00 MB

Capacity Used: 0.00 MB (0.00%)

The total capacity for recording may vary depending on different models. Please check the actual display of your model.

3.6 Trigger

3.6.1 Trigger

You can configure how this camera reacts when there's an alarm, a motion or a PIR event.

Detect

External Alarm: ON

Motion: ON

PIR: ON

Duration: 10 Sec.

Action

E-Mail: External Alarm Motion PIR

FTP: External Alarm Motion PIR

SMS: External Alarm Motion PIR

Alarm Out: External Alarm Motion PIR

Record: External Alarm Internal Alarm

Audio Alert: Manual Alarm-Out

Save Reload

◆ Detect

Item	Description
External Alarm	Enable or disable detection from external alarm-in device, and click the title "External Alarm" (in blue) to set "N.O." or "N.C." depending on the configuration of your alarm-in device.
Motion	Enable or disable motion detection. <i>Motion detection is not supported when the stream format is Motion JPEG.</i> When "Enable" is selected, click "Detection" to enter the motion detection area setting page as follows:
	<p>Detection Configuration</p> <p>Sensitivity: Normal</p> <p>Select All Clear All</p> <p>Save Reload Back</p>
	Sensitivity: Set the detection sensitivity from the drop-down list: High, Normal or Low.
	Area Setting: Set the motion detection area by selecting the area grids with your mouse. Pink grids represent the area that is not being detected while the transparent grids are the area under detection. You can set multiple areas under detection. Click "Clear All" to set the whole area undetected. Click "Select All" to set the whole area under detection.
PIR*	Enable (ON) or disable (OFF) PIR detection.
Duration	Set the duration time for trigger recording (5 / 10 / 20 / 40 seconds).

*Selected models only

◆ Action

Here defines how the camera delivers alerts to you for any event.

Item	Description
E-Mail	Select the event type you want to receive E-mail notifications when it occurs. Then, click the title "E-Mail" (in blue) to configure the media type (H264 / JPEG / MPEG4), file format (AVC / AVI), and record time (1 ~ 5 seconds) for the event video clip. The camera will send the captured video clip to the E-mail address(s) you assigned in "Network" → "Mail" once the selected event type occurs.
FTP	Select the event type you want to receive FTP notifications when it occurs. Then, click the title "FTP" (in blue) to configure the media type (H264 / JPEG / MPEG4), file format (AVC / AVI), and record time (1 ~ 5 seconds) for the event video clip. The camera will upload the captured video clip to the FTP site you assigned in "Network" → "FTP" once the selected event type occurs.
SMS	Select the event type you want to receive a text message when it occurs. The camera will send a text message to the mobile phone number you assigned in "Network" → "SMS" once the selected event type occurs.
Alarm Out	Select the event type you want to trigger the alarm-out device to work when it occurs. Then, click the title "Alarm Out" (in blue) to configure the trigger rule (LOW / HIGH).
Record	Select the event type you want to enable event recording when it occurs.
Audio Alert*	Select the event type you want to enable audio alert when it occurs.

*Selected models only

3.7 General

3.7.1 General

To change the language of UI interface, select from the drop-down list in "Language".


To allow the status LED indicators to show the status as indicated in "1.6 Status Indicator (For Type 1 only)" at page 2, select "Enable" in "Status LED Mode"; to hide the status, select "OFF"; to only show the error status, select "Temporary Disable".

Note: LED indication is available for selected models only.

Note: The status LED mode will be restored to "Enable" after camera reboot when "Temporary OFF" is selected.

To lock camera access when it's not used after the specified time, select "5 MIN", "15 MIN" or "30 MIN" from the drop-down list of "Auto Lock Time", or select "NEVER" to disable this function.

Note: When the camera access is locked after the specified time, to resume camera access, please enter the password.



3.7.2 Time

Set daylight saving time and the current time, and click “Save” to confirm.

Time

Time Configuration

OSD: Enable Disable

Date: 2011/08/30

Time: 21 : 16 : 41

Daylight Saving Time

Daylight Saving Time Configuration

Daylight Saving Time: Enable Disable

Start Time: August First Week Monday 6 : 0 (HH:MM)

End Time: October Fifth Week Monday 10 : 0 (HH:MM)

Adjust Time: 1 : 0 (HH:MM)

Function	Description
■ Time Configuration	
Date	Set the current date.
Time	Set the current time.
■ Daylight Saving Time Configuration	
Daylight Saving Time	Specify whether to use daylight saving time (Enable / Disable). If this function is enabled, set the time period (Start Time / End Time), and adjust the daylight saving time in hours (Adjust Time).

3.7.3 Server Log

To quickly search the system logs you want by event type, click “Prev. Page” or “Next Page” to find the logs you want, or check the event type(s) and click “Reload” to start searching.

To clear all system event logs, click “Clear All”.

Server Log List			
No.	Event	Time	Result
1	Remote Login	2011/08/30 20:54:41	admin
2	Remote Login	2011/08/30 20:29:58	admin
3	Remote Login	2011/08/30 18:22:08	admin
4	SNTP Update	2011/08/30 18:20:06	Failed
5	Remote Login	2011/08/30 18:20:03	admin
6	Power On	2011/08/30 18:19:24	ON
7	Power On	2011/08/30 18:18:46	OFF
8	Remote Login	2011/08/30 18:11:21	admin
9	Remote Login	2011/08/30 18:11:18	admin
10	Remote Login	2011/08/30 18:07:10	admin
11	Remote Login	2011/08/30 18:03:19	admin
12	Remote Login	2011/08/30 18:02:15	admin
13	Remote Login	2011/08/30 18:02:07	admin
14	Remote Login	2011/08/30 18:01:51	admin
15	Remote Login	2011/08/30 17:57:01	admin
16	Remote Login	2011/08/30 17:56:55	admin
17	Remote Login	2011/08/30 17:56:53	admin
18	Remote Login	2011/08/30 17:54:44	admin
19	SNTP Update	2011/08/30 17:50:48	Failed
20	Power On	2011/08/30 17:50:07	ON

3.7.4 Online

You can check the current online user(s) with respective online information. To refresh the list, click “Reload”.

- To allow anonymous login, select “Enable” in “Anonymous Viewer Login”.
- To disable image code verification at login, select “No” in “Login with CAPTCHA Image”.

The screenshot shows the 'Online Configuration' page. At the top, there are two radio buttons: 'Anonymous Viewer Login' (Enable) and 'Disable' (selected). Below that is another pair: 'Login with CAPTCHA Image' (Yes) and 'No' (selected). A text input field 'Max Online User:' contains the value '10'. Below these settings is a table listing online users:

Username	IP Address	User Level	Media Type
admin	211.75.84.96	SUPERVISOR	H264
admin	60.248.97.4	SUPERVISOR	H264

At the bottom of the page are three buttons: 'Save', 'Reload' (highlighted with a blue border), and another 'Reload' button.

3.7.5 Account

You can create a new account with different user access privilege, or delete or modify an existing account setting.

How to create a new account

Step1: Click “New”, and fill in the following columns.

The screenshot shows the 'Account' management interface. On the left, a list of existing accounts: admin (SUPERVISOR, INFINITE), power (POWER USER, 1 HOUR), normal (NORMAL, 1 HOUR), and guest. On the right, a modal dialog titled 'New Account Info' is open, prompting for new account details:

Username:	office
Password:	*****
Confirm Password:	*****
User Level:	POWER USER
Life Time:	1 HOUR

Below the dialog are 'Save' and 'Close' buttons. A red arrow points from the left towards the 'Add' button in the main interface, which is highlighted with a blue border.

Column	Description
User Name	Set a user name that will be used for camera access. The user name allows up to 16 alphanumeric characters.
Password	Set the password that will be used for remote login. The password allows up to 16 alphanumeric characters.
Confirm Password	Enter the password again to confirm.
User Level	Set the security level of an account to give the permission to control different functions. There are four user levels: SUPERVISOR, POWER USER, NORMAL USER and GUEST.
Life Time	Select how long this account is allowed to stay online (1 MIN / 5 MIN / 10 MIN / 1 HOUR / 1 DAY / INFINITE)

Step2: Then, click “Save” to save your setting and create a new account.

How to modify or delete an existing account

Step1: Select the account you want to modify or delete.

Step2: To modify the account, click “Edit” to change the settings, and click “Save”.

To remove the account, click “Delete”.

Note: It's not allowed to remove an account when there's only one account in the account list.

3.7.6 Google Maps


This function is used to let you know where the network camera is.

The system will prompt you to apply a Goole Maps Key if your access is denied. Please follow the instructions below when you're denied:

Step1: Click “Sign up for a Google Maps key” to enter the application page.

Step2: Check the terms and conditions, and enter the IP address of the network camera. Then, click “Generate API Key”.

Step3: Copy the generated API key, and click “Update Google Maps Key” on the web browser to paste it.



3.7.7 Maintenance


Firmware Upgrade

This function is used when users need to upgrade the camera for function scalability.

Note: Before using this function, make sure you have the correct upgrade files provided by your installer or distributor.

Note: The event videos saved in the camera will be removed after firmware upgrade. Make sure you've copied important events to your PC before firmware upgrade.

Step1: Select “” to browse to where you save the upgrade files, and select them one by one until all files are selected (up to four files).



Step2: Select “Upgrade” to start system upgrading.

Note: You'll be prompted to keep current configurations. It's recommended to keep them, or all configurations will be restored to default values after upgrade.


Note: It takes a few minutes to finish the upgrade process. Do not disconnect the power during firmware upgrade, or the upgrade may be failed. The camera will reboot after the upgrade.

System Configuration Backup

This function is used to copy your system configuration to a “System.bin” file.


You may import the same system configuration to another camera, or restore your system configuration when the camera is reset to default values.

Select “System.bin” in “Firmware Upgrade”, and select “Upgrade” to import the system configuration.



System Reboot

Select “Reboot” to restart your camera if needed.



Player Download

To see the event video clips downloaded to your PC, you need to first install our own video player in your PC. Select “Free Download” to download the video player, and double click the file to install it.



APPENDIX 1 PRODUCT SPECIFICATIONS

	Model 1	Model 2
■ Network		
LAN Port	YES	
LAN Speed	10/100 Based-T Ethernet	
Supported Protocols	DDNS, PPPoE, DHCP, NTP, SNTP, TCP/IP, ICMP, SMTP, FTP, HTTP, RTP, RTSP, RTCP, IPv4, Bonjour, UPnP, DNS, UDP, IGMP, QoS	
ONVIF Compatible	YES	
Number of Online Users	10	
Security	(1) Multiple user access levels with password (2) IP address filtering (3) Digest authentication	
Remote Access	(1) Internet Explorer on Windows operating system (2) EagleEyes on iOS & Android devices	
■ Video		
Network Compression	H.264 / MJPEG	
Video Resolution	1080P to CIF	
Frame Rate	30 / 25fps	
Multiple Video Streaming	4 (H.264, MJPEG)	
■ General		
Image Sensor	1/2.9" CMOS image sensor	
Min Illumination	0.1 Lux / F1.5, 0 Lux (LED ON)	0.1 Lux / F1.4, 0 Lux (LED ON)
Shutter Speed	1/10,000 ~ 1/7.5 (Slow shutter)	
S/N Ratio	More than 48dB (AGC off)	
Lens	f3.8mm / F1.5	f2.8 ~ 12mm / F1.4 ~ F2.8
Viewing Angle	73.2° (Horizontal) / 42.8° (Vertical) / 83.2° (Diagonal)	Wide: 97.4° (Horizontal) / 58.1° (Vertical) / 111.7° (Diagonal) Tele: 27.1° (Horizontal) / 15.2° (Vertical) / 31.1° (Diagonal)
IR LED	1 unit	3 units
IR Effective Distance	15 meters	Default: up to 30 meters; IR Enhanced Mode: up to 50 meters
PIR Sensor	Detection Range 76° wide angle with up to 5m long distance at 2.5m height (under 30°C)	--
IR Shift	YES	
Smart Light Control	YES	
White Balance	ATW	
AGC	Auto	
IRIS Mode	AES	
WDR	YES	
POC (Power-over-Coaxial)	YES	
External Alarm I/O	YES (1 input 1 output)	
Micro SD Card Slot	YES	
Vandal Resistance	--	IK10
Weather Resistance	--	IP66
Operating Temperature	0°C~40°C	-20°C~40°C
Power Source ($\pm 10\%$)	12V / 1A	12V / 1.5A
Current Consumption ($\pm 10\%$)	463mA	849mA
■ Audio		
Line in	YES	
Line out	YES	
■ Others		
Mobile Surveillance	iPad / iPhone / Android mobile device	
Event Notification	FTP / Email / SMS	

	Model 1	Model 2
3 Axis		YES
Digital Pan / Tilt / Zoom		YES
Motion Detection		YES
RTC (real-time clock)		YES
Minimum Web Browsing Requirements	<ul style="list-style-type: none"> • Intel core i3 or higher, or equivalent AMD • 2GB RAM • AGP graphics card, Direct Draw, 32MB RAM • Windows 7, Windows Vista & Windows XP, DirectX 9.0 or later • Internet Explorer 7.x or later 	

* The specifications are subject to change without notice. ** Dimensional tolerance: ± 5mm


APPENDIX 2 BIT RATE TABLE FOR REFERENCE

The data below is for reference only.

The bit rates listed here may vary depending on the resolution, image quality & frame rate you choose, the complexity of your monitoring area, and how often the moving objects show in your monitoring area.

Testing Environment

- Place: Office Entrance
- Network translation: H.264
- Camera type: Megapixel camera



Static: No one coming in and out



Dynamic: One or two people coming in and out

Resolution	Quality	Frame Rate	(Dynamic) kbps	(Static) kbps
SXGA	Best	FULL	3253	3216
	High		2375	2160
	Normal		1571	1266
	Basic		1465	873
VGA	Best		2010	1261
	High		1042	1034
	Normal		685	572
	Basic		457	350
QVGA	Best		646	366
	High		482	350
	Normal		302	286
	Basic		168	161
SXGA	Best	1/4	1163	1076
	High		989	715
	Normal		855	534
	Basic		719	443
VGA	Best		789	571
	High		451	447
	Normal		349	237
	Basic		217	165
QVGA	Best		269	147
	High		182	131
	Normal		164	113
	Basic		97	71

Resolution	Quality	Frame Rate	(Dynamic) kbps	(Static) kbps
SXGA	Best	1/15	581	374
	High		405	342
	Normal		487	248
	Basic		337	141
VGA	Best		358	79
	High		201	63
	Normal		180	28
	Basic		92	15
QVGA	Best		111	84
	High		99	68
	Normal		97	54
	Basic		58	42

APPENDIX 3 API ID APPLICATION FOR SMS MESSAGING

To allow the camera automatically sending a text message when an event happens, you need to apply an API ID from a mobile messaging company first, such as Clickatell or EVERY8D.


Below shows an example of how to get an API ID from Clickatell.

Note: The SMS messaging may not be totally free. Please check the charge policy of the messaging service you use.

Note: The instructions below are for reference only and may vary when Clickatell's official website is updated.

Please follow the steps below for application.

Step1: Go to <http://www.clickatell.com/login.php>. Sign up an account first.



Step2: Select “Developers Central”, select the location where you want to use this service, and fill in your information to create an account.

The image shows the Clickatell sign-up form for 'Developers Central'. It starts with a question 'Which product would you like to sign up for?' with options for 'Communicator2', 'Developers Central', 'Messenger Pro', 'ICM', and 'Affiliates'. A red arrow points to the 'Developers Central' option. Below this, it asks 'Where would you like to send messages to?' with options for 'Anywhere in the World' (selected) and 'Special Offers: One Country only'. Under 'Anywhere in the World', the 'International' option is highlighted with a red box. A red arrow points to the 'Fill in your information' section, which includes fields for first name, last name, username, mobile number, email address, and a CAPTCHA. A red box also highlights the 'International' option under 'Where would you like to send messages to?'.

Step3: When the account is created, the system will automatically send an Email to your specified Email address with the user name, password, and client ID used to log into the service.

Step4: Click the link within the email to log in, and you will be prompted to validate your mobile phone number. Select

“SEND ACTIVATION CODE”. The system will send an activation code to that number for verification.

Check if you receive a text message from Clickatell, and enter the activation code.

Verify your Mobile Number

For security reasons you are required to verify your mobile number in order to make your first credit purchase and send non-test SMS messages.

Your activation code will be sent to

If this is not your number, please retype your mobile number in the box above and click the "SEND ACTIVATION CODE NOW".

Enter activation code here

Enter your activation code once you have received it on your mobile phone:

Coupon Code:

Step4: In your account, find “Connection Status” and create a connection (API ID).

Note: Information on this page may be delayed by up to 1 minute.

Account Status  View Daily Volumes	Message Delivery Status MT For period 15 April 2013 between 00:00 and 23:59 (GMT+2) Credit Balance: 0 OK Payments Pending: 0 Disabled Credit Balance Alert: Disabled Auto Billing: Disabled SMS Bundle: Disabled SenderID: OK Click here to view a detailed report.
Connection Status There are currently no connections in your account. Click here to create a connection (API ID) Click here	
Message Delivery Status MO For period 15 April 2013 between 00:00 and 23:59 (GMT+2) MO received: 0 Disabled Click here to view a detailed report.	

Step5: Select “HTTP/S”.

Connection Setup

Choose the connection that you would like to add to your account.

HTTPS Click “HTTP/S” <small>Our most popular connection, HTTP is one of the simpler ways to connect to the Clickatell API. It is used as an HTTP/Internet Post.</small>	 Clickatell HTTP/API icon
SMTP (Email to SMS) <small>Another firm favourite, the SMTP API allows messages that are sent via e-mail to be converted to SMS. Popular with customers who already have an e-mail messaging system in place.</small>	
	

Give a meaning name for this connection, and click “Submit and Get API ID”.

Add Connection

HTTP API - Information entered during this step can be modified later.

Description: <input type="text" value="IP_SMS"/>	Give a name for this connection
<small>Required field</small>	
<input type="checkbox"/> Replace Leading Zero (Dial Prefix) ? <input type="checkbox"/> Enable IP Address Restriction (IP Lock Down) ? <input type="checkbox"/> Enable SMS Status Notification (MT Callback) ?	
<input type="button" value="Submit and Get API ID"/> Click	

Step5: An API ID will be generated as follows.

Note: Note down the API ID for SMS notification setting later.

HTTP API

Your HTTP API connection was created successfully. Your connection is live ready for you to send SMS messages.

API ID used for SMS

API ID:	<input type="text" value="3461662"/>
Description:	<input type="text" value="IP_SMS"/>

APPENDIX 4 Q&A

For more details about EagleEyes Q&A, please visit our official website: www.eagleeyescctv.com.

Question	Answer
I can connect to this camera in my house or office where it's installed with wireless network. But when I leave my house or office, I can't connect to it from my mobile phone (with 3G network), or other PC (connected to Internet). Why?	You didn't configure this camera to Internet, but only in LAN. Please follow the steps in the advanced network setup guide downloadable from www.surveillance-download.com/user/p521.swf to complete network configurations, or it's recommended for you to check with your local installer or reseller for this service because it's usually hard for a person who doesn't have network knowledge to set network configurations.
My live images are not fluent. Why?	Image fluency could be affected by the local network upload bandwidth, router efficiency, client network download bandwidth, complexity of live view, and more. (Recommended) To have the best image fluency, select QVGA; to have the best image quality, select "HD1080P" or "SXVGA" based on the model you have; to have normal image fluency and quality, select "VGA".
The live video keeps flickering. Why?	Please try adjusting the power line frequency to "60 Hz" or "50 Hz" for the camera. For iPhone users, access the camera, and select "⚙️" on the top right corner to enter IPCAM Configuration page. Then, go to "Advance Setup" → "Camera" to change setting. For access from Internet Explorer, log into the camera, and select "Config." → "Camera" → "Video".

APPENDIX 5 RECORDING TIME TABLE

Below shows the estimated total recording time for each recording resolution.

The recording time per resolution is the average value collected from the both alarm trigger conditions indicated in "Testing Environment", and is for reference only.

The time may vary depending on the resolution, image quality & frame rate you choose, the complexity of your monitoring area, and how often the moving objects show in your monitoring area.

Testing Environment

- Place: Office
- Monitoring area: 1.5 meters away from the camera
- Alarm trigger conditions:
 - (1) One person walks by the monitoring area and leaves immediately.
 - (2) Two persons walk by the monitoring area. One goes away immediately, and the other one stays a while and goes away.

Recording Resolution	SXGA	VGA	QVGA
Recording time (second)	25	115	211

APPENDIX 6 MICRO SD CARD COMPATIBLE LIST

Manufacturer	Capacity	Class	Manufacturer	Capacity	Class
ADATA	2GB	--	Transcend	2GB	--
	4GB	Class 6		4GB	Class 2
Apacer	2GB	--		4GB	Class 4
	4GB	Class 4		4GB	Class 6
SanDisk	2GB	--		8GB	Class 6
	4GB	Class 4		16GB	Class 10
	8GB	Class 4	Kingston	2GB	--
	16GB	Class 4		4GB	Class 4
	32GB	Class 4		8GB	Class 4
Verico	2GB	--		32GB	Class 4
	4GB	Class 4	TOSHIBA	16GB	Class 4
	16GB	Class 10	TOPRAM	32GB	Class 10